

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)


PCT

(10) International Publication Number
WO 2005/090785 A1

- (51) International Patent Classification⁷: **F04B 9/10**, 39/12, A23L 3/015
- (21) International Application Number: PCT/GB2005/000536
- (22) International Filing Date: 15 February 2005 (15.02.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0406168.5 19 March 2004 (19.03.2004) GB
- (71) Applicant (for all designated States except US):
STANSTED FLUID POWER (PRODUCTS) LTD
[GB/GB]; 60 The Crest, Sawbridgeworth, Hertfordshire
CM21 0ES (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **FREEMAN, Alan,**
John, Morris [GB/GB]; 60 The Crest, Sawbridgeworth,
Hertfordshire CM21 0ES (GB).
- (74) Agent: **COATES, Ian, Harold**; Marks & Clerk, 45
Grosvenor Road, St Albans AL1 3AW (GB).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: HIGH PRESSURE PUMPING APPARATUS



(57) Abstract: A pressure intensifier assembly comprising:- (i) a high-pressure barrel assembly; (ii) pressurising means; (iii) a first and a second end closure assembly; (iv) a tension frame assembly adapted to resist axial load exerted, in use, along the longitudinal axis of the high-pressure barrel assembly; characterised in that the intensifier assembly further comprises at least one clamping piston adapted to preload the end closure(s) and the high-pressure barrel assembly against the tension frame assembly in order to overbalance anticipated internal end loads.

WO 2005/090785 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.